

Package: openbangsamoro (via r-universe)

August 28, 2024

Type Package

Title An Interface to the OpenBangsamoro Database

Version 0.0.0.9000

Description The OpenBangsamoro initiative supports the use of open statistical, geospatial, and administrative data for transparent, accountable, and participatory decision-making as the Autonomous Region in Muslim Mindanao (ARMM) transforms into the Bangsamoro Autonomous Region in Muslim Mindanao.

License GPL-3

Imports googledrive, googlesheets4

Suggests covr, spelling

Encoding UTF-8

Language en-GB

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

URL <https://panukatan.io/openbangsamoro/>,
<https://github.com/panukatan/openbangsamoro>

BugReports <https://github.com/panukatan/openbangsamoro/issues>

Repository <https://panukatan.r-universe.dev>

RemoteUrl <https://github.com/panukatan/openbangsamoro>

RemoteRef HEAD

RemoteSha 1a9c5807603fa17eb619c531981cc7d53624a784

Contents

bangsa_get_inventory	2
bangsa_get_metadata	2
bangsa_ls	3

Index	4
--------------	----------

bangsa_get_inventory *Get the OpenBangsamoro Database inventory*

Description

Get the OpenBangsamoro Database inventory

Usage

```
bangsa_get_inventory(dataset = c("geospatial", "tabular", "docs", "metadata"))
```

Arguments

dataset A string value from either "geospatial", "tabular", or "docs" specifying the inventory to retrieve.

Value

A tibble of the specified inventory of various datasets available in the OpenBangsamoro Database.

Author(s)

Ernest Guevarra

Examples

```
## Retrieve the geospatial datasets inventory  
bangsa_get_inventory(dataset = "geospatial")
```

bangsa_get_metadata *Get the OpenBangsamoro Database metadata*

Description

Get the OpenBangsamoro Database metadata

Usage

```
bangsa_get_metadata()
```

Value

A tibble containing metadata information regarding the OpenBangsamoro Database.

Author(s)

Ernest Guevarra

Examples

```
bangsa_get_metadata()
```

bangsa_ls	<i>List files and folders within the OpenBangsamoro Google Drive database</i>
-----------	---

Description

A convenience wrapper to [googledrive](#) functions set to specifically access the OpenBangsamoro Google Drive database and list files and folders within.

Usage

```
bangsa_ls(id = "1W8JV4hth_gs1V6efb92HMz0eU2LRYb00")  
  
bangsa_ls_geodata()  
  
bangsa_ls_tabular(id = bangsa_ls()$id[bangsa_ls()$name == "2-Tabular Data"])  
  
bangsa_ls_docs(  
  id = bangsa_ls()$id[bangsa_ls()$name == "3-Development Plans, Studies, and Reports"]  
)
```

Arguments

id	Character vector of the OpenBangsamoro Google Drive id. This is currently set to <i>1W8JV4hth_gs1V6efb92HMz0eU2LRYb00</i>
----	--

Value

A tibble of names and ids of files and folders within the the OpenBangsamoro Google Drive

Author(s)

Ernest Guevarra

Examples

```
bangsa_ls()
```

Index

[bangsa_get_inventory](#), 2
[bangsa_get_metadata](#), 2
[bangsa_ls](#), 3
[bangsa_ls_docs \(bangsa_ls\)](#), 3
[bangsa_ls_geodata \(bangsa_ls\)](#), 3
[bangsa_ls_tabular \(bangsa_ls\)](#), 3

[googledrive](#), 3