

Package: openmarawi (via r-universe)

August 27, 2024

Type Package

Title An Interface to Open Marawi Database

Version 0.0.0.9000

Description The citizens of Marawi have a right to the data and maps about their home city. When problems are complex, helping people find useful maps (access) can aid them both in finding themselves in the map (understanding) and making the map by themselves (ownership). Open data and useful maps can help empower citizens in mapmaking, placemaking, and decision-making because it can help citizens and interested parties in understanding the issues spatially. It is practical in deliberating, deciding, and delivering the rehabilitation of Marawi City.

License GPL (>= 3)

Depends R (>= 2.10)

Imports dplyr, googledrive, readxl, rlang, sf, stringr

Suggests spelling

Encoding UTF-8

Language en-GB

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

URL <https://panukatan.io/openmarawi/>,
<https://github.com/panukatan/openmarawi>

BugReports <https://github.com/panukatan/openmarawi/issues>

Repository <https://panukatan.r-universe.dev>

RemoteUrl <https://github.com/panukatan/openmarawi>

RemoteRef HEAD

RemoteSha 7548307b84e5ce2730589c19a0b17a585f9ddbf4

Contents

<i>get_drive_id</i>	2
<i>marawi_get_armm</i>	3
<i>marawi_get_lanao</i>	4
<i>marawi_get_marawi</i>	5
<i>marawi_ls</i>	6
<i>marawi_maps_get</i>	7
<i>marawi_maps_list</i>	7
<i>marawi_maps_ls</i>	8

Index	9
--------------	----------

<i>get_drive_id</i>	<i>Get Google Drive identifier given a search pattern</i>
---------------------	---

Description

Get Google Drive identifier given a search pattern

Usage

```
get_drive_id(pattern, drive_list)
```

Arguments

<i>pattern</i>	A pattern to search for
<i>drive_list</i>	A dribble (usually produced from one of the <i>marawi_ls()</i> functions) from which to search the pattern from.

Value

A Google Drive identifier

Examples

```
get_drive_id("ARMM", drive_list = marawi_ls())
```

marawi_get_armm	<i>Get ARMM Barangay level data masterlist from the Open Marawi Google Drive Database</i>
-----------------	---

Description

Get ARMM Barangay level data masterlist from the Open Marawi Google Drive Database

Usage

```
marawi_get_armm(  
  dataset = c("metadata", "demographics", "bgyfacilities", "conflict")  
)  
  
marawi_get_armm_all(tabular = TRUE)
```

Arguments

dataset	A string value from either <i>"metadata"</i> , <i>"demographics"</i> , <i>"bgyfacilities"</i> , or <i>"conflict"</i> specifying the masterlist data to retrieve. If not specified, will default to <i>"metadata"</i> .
tabular	Logical. Should output be flattened into a single data.frame? Default is TRUE. If FALSE, output is a list of data.frames for each sheet in the masterlist Excel file.

Value

A tibble or a list of tibbles of the specified masterlist dataset available in the ARMM directory of the Open Marawi Database.

Author(s)

Ernest Guevarra

Examples

```
## Retrieve the metadata dataset of the ARMM directory in the Open Marawi  
## database  
marawi_get_armm(dataset = "metadata")  
## Not run: marawi_get_armm_all()
```

marawi_get_lanao	<i>Get Lanao del Sur Barangay level data masterlist from the Open Marawi Google Drive Database</i>
------------------	--

Description

Get Lanao del Sur Barangay level data masterlist from the Open Marawi Google Drive Database

Usage

```
marawi_get_lanao(
  dataset = c("metadata", "demographics", "bgyfacilities", "estab", "modetranspo",
             "conflict", "privateschools", "health")
)
marawi_get_lanao_all(tabular = TRUE)
```

Arguments

<code>dataset</code>	A string value from either <code>"metadata"</code> , <code>"demographics"</code> , <code>"facilities"</code> , <code>"establishment"</code> , <code>"mode_transport"</code> , <code>"conflict"</code> , <code>"private_schools"</code> , or <code>"health"</code> specifying the masterlist data to retrieve. If not specified, will default to <code>"metadata"</code> .
<code>tabular</code>	Logical. Should output be flattened into a single data.frame? Default is TRUE. If FALSE, output is a list of data.frames for each sheet in the masterlist Excel file.

Value

A tibble or a list of tibbles of the specified masterlist dataset available in the Lanao del Sur directory of the Open Marawi Database.

Author(s)

Ernest Guevarra

Examples

```
## Retrieve the metadata dataset of the Lanao del Sur directory in the Open
## Marawi database
marawi_get_lanao(dataset = "metadata")
## Not run: marawi_get_lanao_all()
```

marawi_get_marawi	<i>Get Marawi Barangay level data masterlist from the Open Marawi Google Drive Database</i>
-------------------	---

Description

Get Marawi Barangay level data masterlist from the Open Marawi Google Drive Database

Usage

```
marawi_get_marawi(
  dataset = c("metadata", "demographics", "movements", "culture", "housing",
             "facilities", "establishments", "modetranspo", "conflict", "publicschools",
             "privateschools", "health")
)
marawi_get_marawi_all(tabular = TRUE)
```

Arguments

dataset	A string value from either <i>"metadata"</i> , <i>"demographics"</i> , <i>"movements"</i> , <i>"culture"</i> , <i>"housing"</i> , <i>"facilities"</i> , <i>"establishments"</i> , <i>"modetranspo"</i> , <i>"conflict"</i> , <i>"publicschools"</i> , <i>"privateschools"</i> , and <i>"health"</i> specifying the masterlist data to retrieve. If not specified, will default to <i>"metadata"</i> .
tabular	Logical. Should output be flattened into a single data.frame? Default is TRUE. If FALSE, output is a list of data.frames for each sheet in the masterlist Excel file.

Value

A tibble or a list of tibbles of the specified masterlist dataset available in the Lanao del Sur directory of the Open Marawi Database.

Author(s)

Ernest Guevarra

Examples

```
## Retrieve the metadata dataset of the Lanao del Sur directory in the Open
## Marawi database
marawi_get_marawi(dataset = "metadata")
## Not run: marawi_get_marawi_all()
```

marawi_ls*List files and folders within the Open Marawi Google Drive database***Description**

A convenience wrapper to [googledrive](#) functions set to specifically access the Open Marawi Google Drive database and list files and folders within.

Usage

```
marawi_ls(id = "1bph1LBRpxwydAvjuggyjmhmq6HhyteY8")
marawi_ls_armm(drive_list)
marawi_ls_lanao(drive_list)
marawi_ls_marawi(drive_list)
```

Arguments

id	Character vector of the Open Marawi Google Drive id. This is currently set to <i>1bph1LBRpxwydAvjuggyjmhmq6HhyteY8</i> which is the id of the Open Marawi Google Drive . Change this if Open Marawi Google Drive is moved.
drive_list	A dribble from which to search for required Google Drive directory.

Value

A dribble of names and ids of files and folders within the specified Google Drive

Author(s)

Ernest Guevarra

Examples

```
marawi_ls()
marawi_ls_armm(drive_list = marawi_ls())
marawi_ls_lanao(drive_list = marawi_ls())
```

<code>marawi_maps_get</code>	<i>Get maps data from Open Marawi Google Drive</i>
------------------------------	--

Description

Get maps data from Open Marawi Google Drive

Usage

```
marawi_maps_get(dsn, layer = NULL)
```

Arguments

- | | |
|--------------------|--|
| <code>dsn</code> | Data source name of map to retrieve. This should be one of the data source names listed in <code>marawi_maps_list</code> |
| <code>layer</code> | Layer name of map to retrieve. If NULL (default), all layers available within dsn will be retrieved. |

Value

An sf object of specified map

Examples

```
##marawi_maps_get(dsn = "Hazards/Faultlines")
```

<code>marawi_maps_list</code>	<i>List of available map files in the Open Marawi Google Drive</i>
-------------------------------	--

Description

List of available map files in the Open Marawi Google Drive

Usage

```
marawi_maps_list
```

Format

A data frame with 4 columns and 391 rows:

Variable	Description
<i>dsn</i>	Data source name
<i>layer</i>	Layer name
<i>name</i>	Filename
<i>id</i>	Google Drive identifier

Examples

```
marawi_maps_list
```

<code>marawi_maps_ls</code>	<i>List Marawi maps</i>
-----------------------------	-------------------------

Description

List Marawi maps

Usage

```
marawi_maps_ls(id = "1Fj5sK2tKo0_v8EnEbN8m1pMfaSFADmYL")
```

Arguments

<code>id</code>	Character value of the Open Marawi Google Drive id for the Marawi geospatial directory. This is currently set to <code>1Fj5sK2tKo0_v8EnEbN8m1pMfaSFADmYL</code> which is the id of the current id of the Open Marawi Google Drive for the Marawi geospatial directory. Change this if Open Marawi Google Drive is moved.
-----------------	---

Value

A dribble of all the geospatial files for Marawi found in the Open Marawi **Google Drive**.

Examples

```
## Not run:
marawi_maps_ls()

## End(Not run)
```

Index

```
* datasets
    marawi_maps_list, 7

get_drive_id, 2
googledrive, 6

marawi_get_armm, 3
marawi_get_armm_all (marawi_get_armm), 3
marawi_get_lanao, 4
marawi_get_lanao_all
    (marawi_get_lanao), 4
marawi_get_marawi, 5
marawi_get_marawi_all
    (marawi_get_marawi), 5
marawi_ls, 6
marawi_ls_armm (marawi_ls), 6
marawi_ls_lanao (marawi_ls), 6
marawi_ls_marawi (marawi_ls), 6
marawi_maps_get, 7
marawi_maps_list, 7
marawi_maps_ls, 8
```